

ParLite Led

ParLite Led - # 9165
argento/silver
ParLite Led - # 9165/1
nero/black



KEY FEATURES

- Ideal digital substitute of the analog par can
- World's #1 truss toner
- 75% to 82% energy saving compared to traditional technology at the same brightness
- Cosmetic design for hi-end installations, only 3 kg (7 lbs)
- Thick aluminum, long lasting light source in long lasting body
- Variable light projection angles via quick lens change (standard: 12°; optional: 30°, 13°x40°, 110°)
- No fan, no maintenance, no noise
- Can be transformed in IP 65 at any time
- ETL approved
- Internal/external gel frame (standard size for lighting industry)
- Auto-sensing power 90v-250v
- Smart build "Quick Stand" tucked into yoke

SPECIFICATIONS

- RGB color mixing
- Standard lens 12°
- Electronic dimmer (2 different curves selectable)
- Electronic strobe, synchronized, random, pulse effect
- Flicker free
- Double yoke for easy ground standing or truss hanging

PHYSICAL SIZE

- Length: 208 mm (8.2 in)
- Width: 162 mm (6.4 in)
- Height: 256 mm (10.0 in)
- Weight: 3.5 kg (7.7 lbs)

LIGHT SOURCE

- 36 Luxeon leds, 1.2 W each, 12 Red, 12 Green, 12 Blue

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990

COLOR CHANGERS

- Dmx channels: 6
- Setting and addressing: binary dip switch or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 0.2 A at 230 V, 0.5 A at 115 V
- DMX data in/out: 3 pin locking XLR

OPTIONS

- 30° lens kit (# 9167)
- 40°x13° elliptical lens kit (# 9167/2)
- 110° flood reflector (# 9168)
- Frame for internal frost filter (# 9169)
- Frame for external frost filter (# 9169/1)
- 4 leaf barndoor (# 9164)
- IP 65 rear panel (black: # 08E, silver: # 08/1E)
- 5 pin locking XLR (# 9189)



PinLite Led

SPECIFICATIONS

- RGB color mixing
- Standard lens 12°
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse effect
- Double yoke for easy ground standing or truss hanging

PHYSICAL SIZE

- Length: 127 mm (5.0 in)
- Width: 152.4 mm (6.0 in)
- Height: 127 mm (5.0 in)
- Weight: 1.8 kg (4.0 lbs)

LIGHT SOURCE

- 12 Luxeon leds, 1.2 W each, 4 Red, 4 Green, 4 Blue

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Dmx channels: 6

- Setting and addressing: binary dip switch or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 0.18 A at 230 V, 0.45 A at 115 V
- DMX data in/out: 3 pin locking XLR

OPTIONS

- 30° lens kit (# 9186)
- 40°x13° elliptical lens kit (# 9186/2)
- 110° flood reflector (# 9187)
- Frame for internal frost filter (# 9188)
- Frame for external frost filter (# 9188/1)
- 4 leaf barndoor (# 9164)
- IP 65 rear panel (black: # 10, silver: # 10/1)
- 5 pin locking XLR (# 9189)



PinLite Led - # 9180
argento / silver
PinLite Led - # 9180/1
nero / black

