

StripLite Led

StripLite Led RGB+W 35° - # 8047

1 metro nero/black

StripLite Led RGB+W 12° - # 8047/2

1 metro nero/black



KEY FEATURES

- Ideal digital substitute of the analog strip light
- 75% to 82% energy saving compared to traditional technology at the same brightness
- Cosmetic design for hi-end installations
- Thick aluminum, long lasting light source in long lasting body
- Variable light projection angle to adapt to the application
- No fan, no maintenance, no noise
- ETL approved
- Power and data in and out!
- Internal/external gel frame for diffusion filters

SPECIFICATIONS

- RGB+White color mixing
- Standard lens 12°/35°
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse effect
- Quick camlock clamps, on a modular guide with adjustable position

PHYSICAL SIZE

- Length: 1000 mm (39,4 in)
- Width: 152 mm (6.0 in)
- Height: 95 mm (3.7 in)
- Weight: 7.7 kg (17.0 lbs)

LIGHT SOURCE

- 10 Seoul leds (RGB), 3.2 W each, and 10 Luxeon leds (White 3200 Kelvin), 3.2 W each

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Dmx channels: 10

COLOR CHANGERS

- Setting and addressing: binary dip switch or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable with PowerCon connector without power plug
- Power consumption: 0.5 A at 230 V, 1.1 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR

AVAILABLE VERSIONS

- Color mixing system: RGB / RGB+white 3200 K
- Length mm: 500 / 610 /1000 /1220 mm (19.7 / 24.0 / 39.4 / 48.0 in)
- Protection rating: IP20 - IP65
- N° led: 10 / 12 / 20 / 24

OPTIONS

- 2 ground-standing feet (# 8052)
- Frame for internal filter (#8054/2)
- Frame for external filter (#8055/2)



RazorLite Led

SPECIFICATIONS

- RGB color mixing
- Standard lens 12° x 24°
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse effect
- Quick camlock clamps, on a modular guide with adjustable position

PHYSICAL SIZE

- Length: 1000 mm (39.4 in)
- Width: 152 mm (6.0 in)
- Height: 95 mm (3.7 in)
- Weight: 7.7 kg (17.0 lbs)

LIGHT SOURCE

- 36 Luxeon leds, 1.2 W each, 12 Red, 12 Green, 12 Blue

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990

- Dmx channels: 6
- Setting and addressing: binary dip switch or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable (with PowerCon connector) without power plug
- Power consumption: 0.4A at 230 V, 0.9 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR

OPTIONS

- 30° lens kit (# 9167)
- 2 ground-standing feet (# 8052)



RazorLite Led - # 8056
nero / black

