

ParLite Led



ParLite Led IP 65 - # 9166
argento/silver
ParLite Led IP 65 - # 9166/1
nero/black

SPECIFICATIONS

- RGB color mixing
- Standard lens 12°
- Electronic dimmer (2 different curves selectable)
- Electronic strobe, synchronized, random, pulse effect
- Flicker free
- IP 65 weatherproof rating
- Double yoke for easy ground standing or truss hanging

PHYSICAL SIZE

- Length: 208 mm (8.2 in)
- Width: 162 mm (6.4 in)
- Height: 256 mm (10.0 in)
- Weight: 3.5 kg (7.7 lbs)

LIGHT SOURCE

- 36 Luxeon leds, 1.2 W each, 12 Red, 12 Green, 12 Blue

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Dmx channels: 6
- Setting and addressing: binary dip switch or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 0.2 A at 230 V, 0.5 A at 115 V
- DMX data in/out: 3 pin locking XLR

OPTIONS

- 30° lens kit (# 9167)
- 40°x13° elliptical lens kit (# 9167/2)
- 110° flood reflector (# 9168)
- Frame for internal frost filter (# 9169)
- Frame for external frost filter (# 9169/1)
- 4 leaf barndoor (# 9164)
- 5 pin locking XLR (# 9189)



PinLite Led



PinLite Led IP 65 - # 9181
argento / silver
PinLite Led IP 65 - # 9181/1
nero / black

SPECIFICATIONS

- RGB color mixing
- Standard lens 12°
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse effect
- IP 65 weatherproof rating
- Double yoke for easy ground standing or truss hanging

PHYSICAL SIZE

- Length: 127 mm (5.0 in)
- Width: 152.4 mm (6.0 in)
- Height: 127 mm (5.0 in)
- Weight: 1.8 kg (4.0 lbs)

LIGHT SOURCE

- 12 Luxeon leds, 1.2 W each, 4 Red, 4 Green, 4 Blue

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Dmx channels: 6

- Setting and addressing: binary dip switch or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 0.18 A at 230 V, 0.45 A at 115 V
- DMX data in/out: 3 pin locking XLR

OPTIONS

- 30° lens kit (# 9186)
- 40°x13° elliptical lens kit (# 9186/2)
- 110° flood reflector (# 9187)
- Frame for internal frost filter (# 9188)
- Frame for external frost filter (# 9188/1)
- 4 leaf barndoor (# 9164)
- 5 pin locking XLR (# 9189)



StageLite Led



StageLite Led IP 65 - # 8063/1

SPECIFICATIONS

- RGB+White color mixing
- 2 cells, individually controllable, of 48 leds each
- Proportional zoom 11° - 34° (vertical beam, ½ peak angle)
- The light beam is generated by three independent optical planes (**Patent Pending**)
- Orientable beam from + 56° to - 52°; linear adjustment with digital positioning control: concentrate, symmetrical or asymmetrical
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse effect
- Swing effects
- Flicker free, led frequency controlled by DMX
- Orientable standing feets
- Quick camlock clamps, on a modular guide with adjustable position
- IP 65 weatherproof rating

PHYSICAL SIZE

- Length: 609 mm (24 in)
- Width: 211 mm (8.3 in)
- Height: 181 mm (7.1 in)
- Weight: 12 kg (26.4 lbs)

LIGHT SOURCE

- 96 Luxeon leds, 1.2 W each, 24 Red, 24 Green, 24 Blue, and 24 White (6500 Kelvin)

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Dmx channels: 16
- Setting and addressing: led display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable with PowerCon connector without power plug
- Power consumption: 1 A at 230 V, 2 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR

