

Panorama Led RGB



- Panorama Led RGB - # 9841/G**
grigio / grey
- Panorama Led RGB - # 9841/N**
nero / black

SPECIFICATIONS

- RGB color mixing
- Standard lens flood reflector 110°
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse effect
- IP 65 weatherproof rating

PHYSICAL SIZE

- Length: 232 mm (9,13 in)
- Width: 336 mm (13,22 in)
- Height: 116 mm (9,92 in)
- Weight: 4,5 kg (9,92 lbs)

LIGHT SOURCE

- 36 Luxeon leds, 1.2 W each, 12 Red, 12 Green, 12 Blue

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990

- Dmx channels: 6
- Setting and addressing: binary dip switch or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 0.2 A at 230 V, 0.5 A at 115 V
- DMX data in/out: 3 pin locking XLR

AVAILABLE VERSIONS

- Also available upon request with white led 6500 K

OPTIONS

- 12° lens kit (# 9844)
- 30° lens kit (# 9845)



Panorama Power MK2



Panorama Power MK2 - # 9823

SPECIFICATIONS

- CMY color mixing
- Beam angle: 17° - 134°
- 3 different interchangeable diffusion filters: wide, horizontal and vertical beam
- 4 leaf-barndoor
- Dimmer
- TLT dual lamp system (**Exclusive Coemar Patent**)
- IP 44 weatherproof rating

PHYSICAL SIZE

- Length: 430 mm (16.93 in)
- Width: 540 mm (21.26 in)
- Height: 760 mm (29.92 in)
- Weight: 47.5 Kg - (103.0 lbs)

LAMP AND BALLAST

- Type: 2 x Philips 575 MSR/2
- Color temperature: 7200 Kelvin
- Color rendering index: 80

- Average lamp life: 1000 hours
- Socket: GX 9.5
- 2 electromagnetic ballast

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Dmx channels: 6
- Setting and addressing: led display or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 208/230/240 V, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 7 A at 230 V
- DMX data in/out: 3 pin locking XLR

OPTIONS

- 360° rotating support for suspension (# 9821)
- Maxi diffuser (# 9822)
- Narrow beam lens (# KIT43)

